



Perfiles normalizados PLETINAS



Código	a mm	b mm	Aleación	M _{lx} cm ⁴	M _{ly} cm ⁴	W _x cm ³	W _y cm ³
1.03.100	10	2,5	6060/6063-T5	0,001	0,021	0,010	0,042
1.03.120	15	3,0	6060/6063-T5	0,003	0,084	0,023	0,113
1.03.210	20	2,0	6060/6063-T5	0,001	0,133	0,013	0,133
1.03.212	20	3,0	6060/6063-T5	0,005	0,200	0,030	0,200
1.03.214	20	4,0	6060/6063-T5	0,011	0,267	0,053	0,267
1.03.216	20	5,0	6060/6063-T5	0,021	0,333	0,083	0,333
1.03.228	20	10,0	6060/6063-T5	0,167	0,667	0,333	0,667
1.03.240	25	2,0	6060/6063-T5	0,002	0,260	0,017	0,208
1.03.242	25	3,0	6060/6063-T5	0,006	0,391	0,038	0,313
1.03.244	25	4,0	6060/6063-T5	0,013	0,521	0,067	0,417
1.03.246	25	5,0	6060/6063-T5	0,026	0,651	0,104	0,521
1.03.256	25	12,0	6060/6063-T5	0,360	1,563	0,600	1,250
21.82.006.256.03	25	12,0	6082-T6	0,360	1,563	0,600	1,250
1.03.280	30	3,0	6060/6063-T5	0,007	0,675	0,045	0,450
1.03.282	30	4,0	6060/6063-T5	0,016	0,900	0,080	0,600
1.03.284	30	5,0	6060/6063-T5	0,031	1,125	0,125	0,750
21.82.006.284.03	30	5,0	6082-T6	0,031	1,125	0,125	0,750
1.03.286	30	6,0	6060/6063-T5	0,054	1,350	0,180	0,900
1.03.290	30	10,0	6060/6063-T5	0,250	2,250	0,500	1,500
21.82.006.290.03	30	10,0	6082-T6	0,250	2,250	0,500	1,500
1.03.296	30	15,0	6060/6063-T5	0,844	3,375	1,125	2,250
21.82.006.299.03	30	25,0	6082-T6	3,906	5,625	3,125	3,750
1.03.306	35	5,0	6060/6063-T5	0,036	1,786	0,146	1,021
1.03.320	40	2,0	6060/6063-T5	0,003	1,067	0,027	0,533
1.03.324	40	4,0	6060/6063-T5	0,021	2,133	0,107	1,067
1.03.326	40	5,0	6060/6063-T5	0,042	2,667	0,167	1,333
21.82.006.328.03	40	6,0	6082-T6	0,072	3,200	0,240	1,600
1.03.330	40	8,0	6060/6063-T5	0,171	4,267	0,427	2,133
21.82.006.330.03	40	8,0	6082-T6	0,171	4,267	0,427	2,133
1.03.332	40	10,0	6060/6063-T5	0,333	5,333	0,667	2,667
21.82.006.332.03	40	10,0	6082-T6	0,333	5,333	0,667	2,667
1.03.334	40	12,0	6060/6063-T5	0,576	6,400	0,960	3,200
21.82.006.334.03	40	12,0	6082-T6	0,576	6,400	0,960	3,200
1.03.340	40	15,0	6060/6063-T5	1,125	8,000	1,500	4,000

M_{lx}: momento de inercia respecto al eje x. W_x: módulo de flexión respecto al eje x.
M_{ly}: momento de inercia respecto al eje y. W_y: módulo de flexión respecto al eje y.

- Acabados: bruto de fabricación, anodizados y lacados.
- Longitud de suministro: 6.000 mm

* Bajo pedido se pueden suministrar longitudes diferentes de la estándar y/o cortados a medida.



Perfiles normalizados PLETINAS



Código	a mm	b mm	Aleación	M Ix cm ⁴	M Iy cm ⁴	W x cm ³	W y cm ³
21.82.004.340.03	40	15,0	6082-T4	1,125	8,000	1,500	4,000
1.03.350	40	20,0	6060/6063-T5	2,667	10,667	2,667	5,333
21.82.006.350.03	40	20,0	6082-T6	2,667	10,667	2,667	5,333
1.03.360	40	26,0	6060/6063-T5	5,859	13,867	4,507	6,933
1.03.410	50	3,0	6060/6063-T5	0,011	3,125	0,075	1,250
1.03.414	50	5,0	6060/6063-T5	0,052	5,208	0,208	2,083
21.82.006.414.03	50	5,0	6082-T6	0,052	5,208	0,208	2,083
1.03.424	50	10,0	6060/6063-T5	0,417	10,417	0,833	4,167
21.82.004.424.03	50	10,0	6082-T4	0,417	10,417	0,833	4,167
1.03.428	50	12,0	6060/6063-T5	0,720	12,500	1,200	5,000
21.82.006.428.03	50	12,0	6082-T6	0,720	12,500	1,200	5,000
1.03.436	50	15,0	6060/6063-T5	1,406	15,625	1,875	6,250
21.82.006.436.03	50	15,0	6082-T6	1,406	15,625	1,875	6,250
1.03.444	50	20,0	6060/6063-T5	3,333	20,833	3,333	8,333
21.82.006.444.03	50	20,0	6082-T6	3,333	20,833	3,333	8,333
1.03.448	50	25,0	6060/6063-T5	6,510	26,042	5,208	10,417
1.03.452	50	30,0	6060/6063-T5	11,250	31,250	7,500	12,500
21.82.006.452.03	50	30,0	6082-T6	11,250	31,250	7,500	12,500
1.03.472	60	5,0	6060/6063-T5	0,063	9,000	0,250	3,000
21.82.006.472.03	60	5,0	6082-T6	0,063	9,000	0,250	3,000
21.82.006.476.03	60	8,0	6082-T6	0,256	14,400	0,640	4,800
1.03.480	60	10,0	6060/6063-T5	0,500	18,000	1,000	6,000
21.82.006.480.03	60	10,0	6082-T6	0,500	18,000	1,000	6,000
1.03.482	60	12,0	6060/6063-T5	0,864	21,600	1,440	7,200
21.82.006.482.03	60	12,0	6082-T6	0,864	21,600	1,440	7,200
1.03.492	60	20,0	6060/6063-T5	4,000	36,000	4,000	12,000
21.82.006.492.03	60	20,0	6082-T6	4,000	36,000	4,000	12,000
1.03.498	60	40,0	6060/6063-T5	32,000	72,000	16,000	24,000
1.03.510	70	5,0	6060/6063-T5	0,073	14,292	0,292	4,083
1.03.520	70	10,0	6060/6063-T5	0,583	28,583	1,167	8,167
21.82.006.520.03	70	10,0	6082-T6	0,583	28,583	1,167	8,167
1.03.540	70	35,0	6060/6063-T5	25,010	100,042	14,292	28,583
1.03.560	75	15,0	6060/6063-T5	2,109	52,734	2,813	14,063
21.82.006.560.03	75	15,0	6082-T6	2,109	52,734	2,813	14,063



Perfiles normalizados PLETINAS



Código	a mm	b mm	Aleación	M Ix cm ⁴	M Iy cm ⁴	W x cm ³	W y cm ³
1.03.570	80	5,0	6060/6063-T5	0,083	21,333	0,333	5,333
21.82.006.570.03	80	5,0	6082-T6	0,083	21,333	0,333	5,333
1.03.574	80	8,0	6060/6063-T5	0,341	34,133	0,853	8,533
21.82.006.574.03	80	8,0	6082-T6	0,341	34,133	0,853	8,533
1.03.576	80	10,0	6060/6063-T5	0,667	42,667	1,333	10,667
21.82.006.576.03	80	10,0	6082-T6	0,667	42,667	1,333	10,667
1.03.582	80	15,0	6060/6063-T5	2,250	64,000	3,000	16,000
21.82.006.582.03	80	15,0	6082-T6	2,250	64,000	3,000	16,000
1.03.590	80	20,0	6060/6063-T5	5,333	85,333	5,333	21,333
21.82.006.590.03	80	20,0	6082-T6	5,333	85,333	5,333	21,333
1.03.596	80	30,0	6060/6063-T5	18,000	128,000	12,000	32,000
1.03.602	80	50,0	6060/6063-T5	83,333	213,333	33,333	53,333
21.82.006.602.03	80	50,0	6082-T6	83,333	213,333	33,333	53,333
1.03.626	100	5,0	6060/6063-T5	0,104	41,667	0,417	8,333
1.03.630	100	8,0	6060/6063-T5	0,427	66,667	1,067	13,333
21.82.006.630.03	100	8,0	6082-T6	0,427	66,667	1,067	13,333
1.03.632	100	10,0	6060/6063-T5	0,833	83,333	1,667	16,667
21.82.006.632.03	100	10,0	6082-T6	0,833	83,333	1,667	16,667
1.03.634	100	12,0	6060/6063-T5	1,440	100,000	2,400	20,000
21.82.006.634.03	100	12,0	6082-T6	1,440	100,000	2,400	20,000
1.03.640	100	20,0	6060/6063-T5	6,667	166,667	6,667	33,333
1.03.646	100	27,0	6060/6063-T5	16,403	225,000	12,150	45,000
1.03.690	120	10,0	6060/6063-T5	1,000	144,000	2,000	24,000
1.03.698	120	20,0	6060/6063-T5	8,000	288,000	8,000	48,000
21.82.006.698.03	120	20,0	6082-T6	8,000	288,000	8,000	48,000
1.03.740	130	15,0	6060/6063-T5	3,656	274,625	4,875	42,250
1.03.760	140	10,0	6060/6063-T5	1,167	228,667	2,333	32,667
1.03.780	150	10,0	6060/6063-T5	1,250	281,250	2,500	37,500
21.82.006.780.03	150	10,0	6082-T6	1,250	281,250	2,500	37,500
1.03.790	150	30,0	6060/6063-T5	33,750	843,750	22,500	112,500
1.03.840	200	10,0	6060/6063-T5	1,667	666,667	3,333	66,667
1.03.844	200	12,0	6060/6063-T5	2,880	800,000	4,800	80,000
1.03.850	200	15,0	6060/6063-T5	5,625	1000,000	7,500	100,000
1.03.858	200	20,0	6060/6063-T5	13,333	1333,333	13,333	133,333