




## Perfiles normalizados TUBO CUADRADO



Código	a mm	b mm	c mm	Aleación	M lx cm <sup>4</sup>	M ly cm <sup>4</sup>	W x cm <sup>3</sup>	W y cm <sup>3</sup>
1.06.165	16	16	1,5	6060/6063-T5	0,308	0,385	0,308	0,385
1.06.215	20	20	1,5	6060/6063-T5	0,637	0,637	0,637	0,637
1.06.220	20	20	2,0	6060/6063-T5	0,787	0,787	0,787	0,787
1.06.255	25	25	1,5	6060/6063-T5	1,303	1,042	1,303	1,042
1.06.260	25	25	2,0	6060/6063-T5	1,635	1,308	1,635	1,308
1.06.315	30	30	1,5	6060/6063-T5	2,321	1,548	2,321	1,548
1.06.330	30	30	1,5CG	6060/6063-T5	2,336	1,557	2,82	1,88
1.06.360	30	30	2,0	6060/6063-T5	2,942	1,961	2,942	1,961
1.06.375	35	35	1,5	6060/6063-T5	3,767	2,153	3,767	2,153
1.06.380	35	35	2,0	6060/6063-T5	4,809	2,748	4,809	2,748
1.06.410	40	40	1,3	6060/6063-T5	5,029	2,515	5,029	2,515
1.06.415	40	40	1,5	6060/6063-T5	5,715	2,858	5,715	2,858
1.06.425	40	40	2,0	6060/6063-T5	7,337	3,668	7,337	3,668
1.06.440	40	40	3,0	6060/6063-T5	10,197	5,099	10,197	5,099
1.06.475	45	45	2,0	6060/6063-T5	10,624	4,722	10,624	4,722
1.06.520	50	50	2,0	6060/6063-T5	14,771	5,908	14,771	5,908
1.06.530	50	50	3,0	6060/6063-T5	20,849	8,340	20,849	8,340
1.06.540	50	50	4,0	6060/6063-T5	26,153	10,461	26,153	10,461
1.06.615	60	60	1,5	6060/6063-T5	20,033	6,678	20,033	6,678
1.06.620	60	60	2,0	6060/6063-T5	26,046	8,682	26,046	8,682
1.06.630	60	60	3,0	6060/6063-T5	37,141	12,380	37,141	12,380
1.06.720	70	70	2,0	6060/6063-T5	41,961	11,989	41,961	11,989
1.06.820	80	80	2,0	6060/6063-T5	63,315	15,829	63,315	15,829
21.82.005.823.06	80	80	4,0	6082-T5	117,384	29,346	117,384	29,346
21.82.006.823.06	80	80	4,0	6082-T6	117,384	29,346	117,384	29,346
1.06.840	100	100	2,5	6060/6063-T5	154,578	30,916	154,578	30,916